

BESANTEK Waterproof pH/Temperature Meter is widely applied to laboratory fields, aquarium, beverage, fish hatcheries, food processing, photography, quality control, school & colleges, swimming pools and water conditions.

Features:

- High accuracy.
- Range: 0.00~14.00 pH.
- Waterproof (standard IP54).
- LCD display (20mm x 27mm).
- Built-in temperature sensor, auto temperature compensation.
- Provided with pH 4.01, pH 7.00 and pH 10.01 buffer.
- Auto calibration for pH 4.01, pH 7.00 and pH 10.01.
- Data hold function for freezing the desired value.
- Friendly easy to use.
- Compact size and light weight.
- Auto power off without operation in 20 minute.
- Microcomputer circuit and intelligent function
- Accessories: Instruction manual, carrying case, buffers and battery.



BST-PH01

Technical Specification:

BST-PH01	
Measuring Range	pH: 0.00~14.00 pH Temperature: 0°C~50°C (32°F~122°F)
Resolution	pH: 0.01pH Temperature: 0.1°C (0.1°F)
Accuracy	pH: ±0.02pH (after calibration) Temperature: ±0.8°C (±1.5°F)
pH Calibration	pH 4.01, 7.00, 10.01, 3 points calibration
Operating Humidity	Less than 80%RH
Power Source	1.5V battery LR44 x 4
Dimensions	188 x 40 x 35 mm (meter with pH electrode)
Weight	82g (electrode included)

Accessories



Ordering Information:

- BST-PH01: Waterproof pH/Temperature Meter.



Safety Standard:

- EN 61000-6-1: 2007, EN 61000-6-3: 2007